

MODEL	CAPACITY (BTU/HR) (Cool / Heat)	OPERATING VOLTAGE (ACV)	OPERATING FREQUENCY	FULL LOAD AMPS	INPUT WATTS	AIR FLOW (C.F.M.)	DIMENSIONS (In.)	WEIGHT (Lbs)
MAS005ATA	5,250	110-120	60 / 50	4.70	525	210	12.5" H 15 3/4" W 12.5" D	58
MAS007ATA	6,670	110-120	60 / 50	7.00	630	210	12.5" H 15 3/4" W 12.5" D	60
MAS009ATA	9,165	110-120	60 / 50	9.45	900	210	12.5" H 15 3/4" W 12.5" D	64
MAS012ATA	11,350	110-120	60 / 50	10.57	1215	350	14 1/4" H 15" W 20" D	84
MAS012GTA	11,985	208-230	60	6.13	1348			
MAS012WTA	12,220	220-240	50	7.10	1562			
MAS016GTA	14,960	208-230	60	8.40	1848	495	14 1/4" H 15" W 20" D	89
MAS016WTA	14,650	220-240	50	8.30	1826			
MAS020GTA	19,840	208-230	60	10.50	2310	495	14" H x 20" W x 20" W	92
MAS020WTA	20,040	220-240	50	10.50	2310			
MAS024GTA	24,200	208-230	60	13.69	3011	750	16" H x 24" W x 24" W	129
MAS024WTA	23,060	220-240	50	12.89	2835			