

MODEL	HP	REFRIGERANT	EVAPORATING TEMPERATURE (°F)			-25°	-20°	-15°	-10°	0°
RMB1-0033	1/3	R134A	CAPACITY (BTU / HR) AT 75 °F WATER IN TEMP.			880	1,120	1,380	1,680	2,300
COMPRESSOR	WEIGHT	DIMENSIONS	G.P.M.	WATER IN	WATER OUT	VOLTAGE	PHASE	HERTZ	R.L.A.	L.R.A.
AFT12C1E	49 LBS	9.5' H x 14' W x 12' D	320	1/2"	1/2"	110-120	1	60	5.1 A.	30.0 A.
MODEL	HP	REFRIGERANT	EVAPORATING TEMPERATURE (°F)			-25°	-20°	-15°	-10°	0°
RMB1-0050	1/2	R134A	CAPACITY (BTU / HR) AT 75 °F WATER IN TEMP.			1,220	1,620	2,060	2,530	3,590
COMPRESSOR	WEIGHT	DIMENSIONS	G.P.M.	WATER IN	WATER OUT	VOLTAGE	PHASE	HERTZ	R.L.A.	L.R.A.
RF18C2E	66 LBS	12' H x 15' W x 13' D	320	1/2"	1/2"	110-120	1	60	12.9 A.	63.3 A.
MODEL	HP	REFRIGERANT	EVAPORATING TEMPERATURE (°F)			-25°	-20°	-15°	-10°	0°
RMB2-0075	3/4	R404A	CAPACITY (BTU / HR) AT 75 °F WATER IN TEMP.			2,240	2,800	3,390	4,020	5,390
COMPRESSOR	WEIGHT	DIMENSIONS	G.P.M.	WATER IN	WATER OUT	VOLTAGE	PHASE	HERTZ	R.L.A.	L.R.A.
R664C2E	71 LBS	13' H x 15' W x 13' D	320	1/2"	1/2"	203-230	1	60	7.7 A.	37.0 A.
MODEL	HP	REFRIGERANT	EVAPORATING TEMPERATURE (°F)			-25°	-20°	-15°	-10°	0°
RMB2-0100	1.0	R404A	CAPACITY (BTU / HR) AT 75 °F WATER IN TEMP.			3,170	3,780	4,430	5,150	6,810
COMPRESSOR	WEIGHT	DIMENSIONS	G.P.M.	WATER IN	WATER OUT	VOLTAGE	PHASE	HERTZ	R.L.A.	L.R.A.
R680C2E	75 LBS	13' H x 15' W x 14' D	320	1/2"	1/2"	203-230	1	60	9.6 A.	46.0 A.